

STEP 1: REMOVE DRIVER'S SEAT FROM CABIN (optional)

At this stage of your truck's life it might be time for a full-blown cabin clean-up. So, removing the driver's seat to do the cushion installation is a good excuse to freshen things up. The seat is easily removed by unbolting the four 13 mm bolts that hold the seat onto the base of the slider.

- Unbolt the seat
- Disconnect the wiring for the seat belt chime and/or power controls
- Remove the driver's seat from the cabin

STEP 2: REMOVAL OF THE SEAT CUSHION COVER

Whether the seat is on a workbench or in the truck, you will next remove the plastic trim (for power seats) and the seat-back adjustment lever from the left side of the driver's seat. To remove the seat-cushion cover, you will have to release the three J-Clips (one in front and one on each side) from the metal edges that they overlap.



In removing the J-Clips, it helps to put on a pair of rubber gloves to protect your hands. Should your hands slip, the gloves will keep your hands from being cut on sharp metal brackets under the seat.

Use moderate force to push the front of the seat-cushion cover down, then push the J-Clip back from the metal edge that the J-Clip fits over. With the front seat cover released, release the two side J-Clips.

STEP 3: REMOVE THE SEAT CUSHION

STEP 4: INSTALL NEW SEAT CUSHION AND REINSTALL THE SEAT COVER

STEP 5: REINSTALL THE SEAT ONTO BASE OF THE SLIDER

As a side note, no doubt you've noticed how easy this project is to do. If you haven't already, give some thought to adding our "Seat Heater Kit" by Rostra Controls. The seat back is just as easy to remove as the seat cushion and seat heat is a great item to have in those Winter months.



If you need more assistance, we are only a phone call away.

(770) 886-2500

Monday-Friday
8:30am-5:30pm EST

GENO'S GARAGE, INC.
1150 Samples Industrial Drive
Cumming, Georgia 30041