

## '03-'05, ('06-'09 Non-Sport) Dodge Turbo Diesel Truck



### **Step 1: Self Tapping Phillips Head Screw**

For a tight fit of cup holder to console, you will want to use the supplied Phillips head screw to hold the cup holder in place. Position the cup holder in place, then press down and forward firmly. Install the self-tapping screw in Location 1 shown above. For a slightly more discrete location and to keep the tight fit, some customers like Location 2.

### **Step 2: Latch Closure**

On latch closure you have to shim the latch with one or two washers.



Removal is easy. Open the lid. There is an outer plastic trim piece that will be loosened and partially removed.

Continued on Next Page ►



If you need more assistance, we are only a phone call away.

**(770) 886-2500**

Monday–Friday  
8:00am–7:00pm EST

**GENO'S GARAGE, INC.**  
1150 Samples Industrial Drive  
Cumming, Georgia 30041

# Installation: Cup Holder



The trim is held in place with clips. Slip your hand under the trim, and then pop the trim loose.



The inner fabric cover is held in place with Velcro. Unfasten the fabric for access to the latch mechanism.



Remove the latch mechanism (two Phillips-head screws), insert the washer(s) behind the latch mechanism (between mechanism and inside of console lid), and then reinstall the latch. Test latch and lid for closure and fit. Install additional washers as needed.

That's it. Enjoy your new cup holder.