



www.genosgarage.com

INSTRUCTIONS

DashSkin Aerosol Colormatched Interior Paint for Dodge Ram Trucks (12 Oz.)

WEATHER CONDITIONS! To prevent a cloudy/hazy finish caused by trapping moisture beneath the coating, only apply aerosol paint when the relative humidity is low (ideally <70%).



- 1) The first step is to check fitment of your part to make certain that any needed trimming or adjusting is done before painting is started. (On a large part like a dash you can even loosely install several bolts to give you a good idea of fitment).
- 2) Clean the surface to be painted using an industrial degreaser (Purple Power, Simple Green, e.g.) and allow to dry completely. Buff the entire surface thoroughly, but gently, with either a Scotch-Brite pad or 600-800 grit sandpaper. Wipe off dust with a clean, soft rag. This process will help remove the glaze and give the paint a better grip. You want to do this carefully so as not to gouge or scratch the surface, only to remove the sheen.
- 3) Shake the can vigorously for one full minute.
- 4) Spray a test surface such as cardboard to ensure the can is mixed well.
- 5) Now you're ready to apply the paint. For best end results, spray multiple, **VERY THIN COATS**, about **8-12 INCHES** from the intended surface. Wait 10 minutes between coats. Continue with this application/10 minutes dry time procedure for 3-6 coats, until you've achieved a nice, even and opaque finish. Allow to air dry - the longer the better before installing the part.

Always follow basic spray paint rules concerning adequate ventilation, wear a mask, and consider overspray potential. The products also list manufacturer's guidelines that should be observed.



If you need more assistance, we are only a phone call away.

(770) 886-2500

Monday-Friday
8:30am-5:30pm EST

www.genosgarage.com

GENO'S GARAGE, INC.
1150 Samples Industrial Drive
Cumming, Georgia 30041